

KV-13B

**Full HD video output**

1/2.8 Sony sensor. supports up to 1080p 30 frames video call, Provides high-definition image quality

**105° Wide View Angle:**

105° wide view angle, without distortion, can easily cover every corner of the conference room, no worries about where your seat is located

**Built-in Microphone**

Integrated One omni-directional microphones and voice pickup range up to 3-5 meters

**Support OSD Menu**

Support adjust video parameters on OSD Menu, More convenient for image setup

**Support EPTZ function**

the electronic pan/tilt rotation and digital zoom function can be realized through the remote control (digital zoom is about 3x)

**Plug and Play**

One USB-C cable for both power supply and video output, reduces wiring make video communication easier

**Multiple installation modes**

Support Tripod, Desktop or Wall mount installation



Specification sheet		
Model no.		KV-13B
Image sensor	Sensor	1/2.8" Sony CMOS
	EffectivePixel	2.1 Megapixel
	White Balance	Auto
	Gain control	Auto
	Backlight Compensation	Support
	Shutter	Support
Lens	S/N Ratio	>50db
	Focus	f=2.26 mm F1.8
	Zoom	Fixed (EPTZ 3x zoom)
	HOV	116.4°(D) / 105° (H) / 56°(V)
Video output		USB 2.0 type C
Video output Format		MJPEG / YUY2 / H264: 1600x896, 320x240, 352x288, 640x480, 720x576, 1280x720, 1024x768, 1024x576, 960x540, 848x480, 800x600, 800x488, 640x360, 480x272, 1920x1080
Special Functions		Support OSD Menu, PIP, EPTZ
Video output Interface		USB 2.0 type C
Audio Parameters		
Microphone		Full duplex 360° omni-directional microphone
Pick up Diameter Range		Max 5 meters
Audio		ANS auto noise suppression, AGC gain control
Sampling Rate		48kHz
Audio Output		USB 2.0 type C
Other Parameters		
Consumption		1.5W max
Power Supply		USB 2.0 5V 0.5A
Status		2 color LED lights
Remote Control		Power on/off, brightness control Zoom in/out, up, down, left, right, OSD menu, PIP mic mute,
UVC Protocol		Support complete UVC protocol, support Zoom Skype and other remote control
Storage Temperature		-40°C~50°C
Working Temperature		-10°C~40°C
Working Humidity		0~95% RH
Dimension (LxWxH)		200.6mm x55.4mm x71.5mm
Weight		198.9g